

Uvitem

Ultravioleta, Tecnología
y Maquinaria, S.L.

Forklift Scale Pallet Trolley

Uvitem includes in the provision a new range of forklift scale pallet trolley.



CE **ATEX**

Forklift scale with built-in electronic weighing,
for dangerous areas classified as hazardous
(ZONES 2 and 22), in accordance with
ATEX II 3GD c IIC T6.

UV – TPLPEX FORKLIFT SCALE PALLET TROLLEY

Main features

- Indicator with 16 numeric/functional keys. Waterproof and stainless steel casing and IP68 protection.
- Backlit LCD display with 6 digits, 25 mm, high brightness and easy readable.
- Extra thick steel sheet structure hot painted.
- Stainless steel forks.
- Steering wheels in rubber
- Double loading rollers in Vulkolan
- 4 shear-beam load cells and IP67 connections.
- Maximum lifting capacity: 2500
- Weight: 120 kg approx
- Fork dimensions: 1170 x 550 x 85mm
- Accuracy: +/- 0.05% of capacity
- Calibration and set-up configurable from keyboard
- Programmable auto power saving function
- Power supply through extractable battery, rechargeable in safe zone.
- 40 hours operating time (approx)
- Equipped with 230Vac 50 Hz battery charger to be recharged in a safe area.
- 2 bidirectional RS232/C serial output.

Keyboard function

- Zero function, automatic tare, print and / or data transmission command, function command (accumulation or counting). Presetable tare, ID. 1 code, ID. 2 code, 10 recallable tare values.

Selectable functions

- Simple visualization and / or high sensibility x 10, Net/gross, In/Out weighing, accumulation (maximum 10 memory records). Tare record (max. 10), formula weighing, counting (maximum resolution of 1.500.000 divisions) with introduction function P.M.U, Lb/kg conversion, Hold, Peak.

MODEL FOR INTERNAL FACTORY USE

<i>Reference</i>	<i>Capacity</i>	<i>Fraction (kg)</i>
UV-TPLPEX15D	600 / 1500	0.2 / 0.5
UV-TPLPEX20	2000	0.5
UV-TPLPEX25D	1500 / 2500	0.5 / 1

MODEL FOR LEGAL USE CE-M

<i>Reference</i>	<i>Capacity</i>	<i>Fraction (kg)</i>
UV-TPLPEX 6M	600	0.2 / 0.5
UV-TPLPEX 15DM	600 / 1500	0.2 / 0.5
UV-TPLPEX 15M	1500	0.5
UV-TPLPEX 25DM	1500 / 2500	0.5 / 1
UV-TPLPEX 25M	2500	1
UV-TPLPEX 20TM	500 / 1000 / 2000	0.5 / 1 / 2