

Balanzas de laboratorio y de precisión

STA

Laboratory scale

- CE certificate
- External case in aluminium
- High contrast LCD display
- Unit of measure: g, mg and ct
- Percentage weighing
- Printer optional. Comply with GMP / GLP directives
- External calibration (E version) or internal calibration (S version)
- RS-232-C serial output
- Optional kit for calculation of density in solids or liquids.



Model	Capacity (g)	Resolution (mg)	Calibration	Plate dimens. (mm)	Scale dimens. (mm)	Power supply
STA-120S	120	0.1	Internal	85 diam.	205x300x90	230V 50 Hz
STA-220S	220					
STA-120E	120		External			
STA-220E	220					

BH



- Laboratory scale
- Backlit display
- Protection against wind
- Antivibration filter
- Settable calibration value
- Percentage weighing
- Counting function
- Version BH-300 calculates weight in m2
- RS-232-C serial output
- 12 weighing units

Model	Capacity (g)	Resolution (g)	Plate dimens. (mm)	Scale dimensions (mm)	Power supply
BH-150	150	0.005	115 diam.	175x226x625	220V-9V/300 mA/ 4 batteries R-14
BH-300	300	0.01			
BH-600	600				
BH-1200	1200	0.02	144x124		
BH-3000	3000	0.1			

AH

- Laboratory scale
- ABS and robust steel case
- Backlit display
- Counting function
- Percentage weighing
- Units of measure: gr, lb, ct.
- Internal rechargeable battery
- Data output RS-232-C and USB
- Wind protection (except AH-3000)



Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
AH-150	150	0.005	116 diam.	200x80x250	Rechargeable battery Power supply 220V/500mA
AH-300	300	0.01			
AH-600	600	0.01			
AH-1200	1200	0.02	124x144		
AH-3000	3000	0.1			

ST



- Laboratory scale
- CE certificate and serial approval optional only in ST-110 version
- External case in aluminium
- High contrast LCD display
- Units of measure: gr, mg, oz, ct.
- Counting function
- Percentage weighing
- Two tare keys
- Printer optional. Comply with GMP / GLP directives
- Data output RS-232-C and USB
- Couple for weighing hook

Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
ST-110	110	0.001	128x128	205x300x90	230V 50 Hz
ST-360	360				
ST-510	510				
ST-1200	1200	0.01	165x165		
ST-2100	2100				
ST-3100	3100				
ST-4100	4100				

AX

- Compact precision scale
- Backlit display
- Last weighing recorded
- Calibration weight included
- Protection lid
- Power supply by batteries or net (220V)



Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
AX-1000	1000	0.1	130 diam.	150x190x40	4 batteries AAA Power supply DC 6V



MS

- Compact and robust structure
- Stainless steel plate
- Counting function
- Backlit display
- Limit function
- Hold function for temporal memory
- Filter to be adapted to unstable environments
- External calibration

Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
MS-3	3000	0.1	198x176	213x275x85	4 batteries UM-2 Power supply 1.5V . DC9V
MS-15	15000	0.5			

MR

- High resolution
- ABS compact and strong structure
- Backlit display
- Stainless steel plate
- Double power supply: 220V and 9V



Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
MR-2500	2500	0.5	198x176	213x275x80	4 batteries UM-2 Power supply 1.5V . DC9V
MR-5000	5000	1			
MR-15K	15000	5			



MM

- ABS external casing
- Stainless steel casing
- High readable display
- Double power supply: 220V and 9V
- Backlit display
- Protection against overload

Model	Capacity (g)	Resolution (g)	Tare range (g)	Plate dimens. (mm)	Scale dimens. (mm)	Power supply
MM-600	600	0.1	600	205x130	210x210x85	Battery 9V Power supply 220V/9V
MM-1200	1200	0.2	1200			
MM-2500	2500	1	2500			
MM-5000	5000	2	5000			
MM-6000	6000	1	6000			

DV

- Protection against liquids IP65
- Fast counting function
- Limit function with acoustic and visual warning
- Double backlit display
- Internal rechargeable battery



Model	Capacity (g)	Resolution (g)	Tare range (g)	Plate dimens. (mm)	Scale dimens. (mm)	Power supply
DV-3	3000	0.5	3000	218x190	242x130x285	9V/300mA
DV-6	6000	1	6000			
DV-15K	15000	2	15000			
DV-30K	30000	5	30000			



DM

- CE certificate and serial approval optional (except DM-1100 and DM-11K)
- Total protection against water IP66
- Double display (except DM-1100 and DM-11K)
- Backlit display
- Protection against overload
- Internal rechargeable battery
- Settable resolution (except DM-1100 and DM-11K)

Model	Capacity (g)	Resolution (g)	Plate dimens. (mm)	Scale dimens. (mm)	Power supply
DM-1100	1100	0.1	250x215	270x278x145	0-40°C
DM-3000	3000	0.5	250x215		
DM-6000	6000	1	250x215		
DM-11K	11000	1	250x215		
DM-15K	15000	2	250x215		
DM-30K	30000	5	250x215		

CM

- High weighting precision
- Counting function
- Weight and number of pieces function with acoustic and visual warning
- Manual or automatic accumulation of weights
- Units of measure: gr, lb
- Data output RS-232-C
- Large backlit display with easy readouts
- Internal rechargeable battery



Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimens. (mm)	Power supply
CM-3	3000	0.1	300x230	310x330x115	Rechargeable Battery Power supply 220V 50/60
CM-6	6000				
CM-15	15000	0.2			
CM-30	30000	0.5			



DS

- Large plate
- Backlit display
- Fast counting function
- Unit of measure: gr, oz
- Overload protection
- Internal rechargeable battery

Model	Capacity (g)	Resolution (g)	Plate dimensions (mm)	Scale dimensions (mm)	Power supply
DS-3000	3000	1	230x300	320x330x120	9V/800 mA
DS-6000	6000	2			
DS-15K	15000	5			
DS-30K	30000	10			